CORE LANDSCAPE Vehicular traffic

2" (50 mm)

ESIN BOUNDED AGGREGATE - overburden HONEYCOMB GRID CONFINEMENT SYSTEM w/ loose chip stone (ASTM #9

> CLEAR AGGREGATE, i.e. ASTM #57 (COMPACTED PER PROJECT ENGINEER'S SPECS)

NATIVE SOILS

*Depth based on local Best Base Practices

The CANA Pave[™] system is comprised of four components:

- 1. ROMPOX® PROFI-DEKO UV resistant 2-part epoxy resin
- 2. CANA Gravel stabilizing grid
- 3. Infill aggregate
- 4. Top surface aggregate

SUITABLE FOR

- Public Projects
- Access Lanes
- Pathways
- Plazas
- Driveways
- Commercial Walkways

FEATURES













2750 Cumberland Rd, Courtenay, BC





Environmentally Approved: Maryland Department of the Environment, Montgomery County, and City of Victoria, British Columbia



LEED: Used in SUDS and LEED Compliant Porous

SGS: ASTM D1621-04A (compressive test standard)

ADA Compliant: Used in ADA Disability Compliant Surfaces for Pedestrians, Biycles,& Wheelchair Traffic

> shop.coregravel.ca +1 855 777 2673

